



3960 Howard Hughes Parkway, Suite 500, Las Vegas, NV 89169
(800) 731-2231, FAX: (866) 361-1558, sales@ndclean.com, www.ndclean.com

GROUT COATING SYSTEM™ **For Ceramic Wall & Floor Tiles**

PROBLEM: Bathroom and kitchen wall and floor grout is discolored and cleaning does not revive it to a "like new appearance". Is there a way to restore it without expensive re-grouting? Can anything be done to eliminate the damage caused by water, mildew, cleaning chemicals, urine from spoiling the uniform color of brand new grout and to correct the appearance of discolored grout in walls and floors?

SOLUTION: Yes! GROUT COATING SYSTEM™ For Ceramic Wall & Floor Tiles is the easiest and the most economical way to restore/recoat discolored grout. It is a proven product for many years that is a coating - not a paint - that makes grout look BRAND NEW! Users have stated that it "looks the same 5 years later". Sealing GROUT COATING with our SKID SAFE Water Based Sealer is mandatory. Now, the sealed floor/wall is protected from water and chemical damages and is extremely slip resistant (ASTM C 1028: COF: .81 Dry, COF: .77 Wet). SKID SAFE does not require stripping! Worn areas can be burnished or reapplied. Save a fortune in labor maintenance costs and make your bathroom look gorgeous.

HOW DOES IT WORK? Our proprietary GROUT COATING is spread over the pre-cleaned/stripped tiles and grout lines. As it dries, it deeply penetrates all grout lines and prevents water damage and discoloration for years. After drying for 24 hours, it is damp mopped off the tiles leaving all grout lines coated in your chosen color. The tiles are now etched with our SUPER BOND & CLEAN™, and next sealed with our SKID SAFE Water Based Sealer/Finish to create a glossy highly slip resistant finish has proven to last for many years and does not require stripping!

WHERE CAN I USE IT? Use GROUT COATING on any ceramic tile, new or used, shiny or dull. Do not spread it over unglazed tile, concrete, slate, nor brick. However, you can apply it directly into the grout of brick and then seal it with SKID SAFE. It can be applied over quarry tile to fill the grout and then be wiped off the tile surface! All grout must be UNSEALED and CLEAN before applying GROUT COATING. If the grout is unsealed, it should be thoroughly cleaned with a neutral cleaner to remove all soils. It is not necessary to clean damaged grout to an even appearance before using GROUT COATING. Even blackened grout can be coated with any of our colors of GROUT COATING, without showing through this amazing product.

HOW CAN IT BE USED? GROUT COATING is designed to be applied to both the grout and tiles simultaneously. This saves a fortune in labor compared to costly re-grouting or an

application over the grout only. When dry, GROUT COATING is easily wiped off tiles yet remains in the grout. It is as easy as mopping a floor or a wall! After drying for 24 hours, it is easily damp mopped/wiped off the surface of the tiles, which leaves the GROUT COATING firmly in place in all grout lines. Now, the tiles are treated with our SUPER BOND & CLEAN™ which provides permanent adhesion for the application of our proprietary SKID SAFE Water Based Sealer/Finish.

HOW CAN I PROTECT A FLOOR TREATED WITH GROUT COATING? After our GROUT COATING has been applied to the floor/wall and allowed to dry for 24 hours, damp mopped off the tiles leaving perfect looking new grout lines, treated with our SUPER BOND & CLEAN™, and the floor/wall is absolutely dry to the touch, the floor/wall must be sealed with our SKID SAFE Water Based Sealer/Finish. This unique product that has lasted for many years under heavy foot traffic protects our GROUT COATING from all discoloration! SKID SAFE does not require stripping. To maintain high gloss of SKID SAFE wash it with clean water, or with a neutral cleaner.

GROUT COATING is available in three basic colors: white, grey and almond.

Our GROUT COATING SYSTEM™ is warranted for 5 years on tile walls/floors when applied and maintained as directed.

04/07