

ND AGGREGATE™

DESCRIPTION:

A special white aluminum oxide which is extremely hard and durable under heavy foot traffic and under the heavy weight of tires and should not be crushed by such weight even after many years! It is lightly broadcast onto our freshly applied SKID SAFE Water Based Sealer/Finish when it is still wet. While the aggregate is white, it will be barely visible, or invisible when standing or sitting in a chair on the floor when lightly broadcast. Its appearance changes to clear when properly top sealed with an additional 5 coats of our SKID SAFE Water Based Sealer/Finish. 1 lb. will cover about 160 sq ft.

DIRECTIONS FOR USE WITH SKID SAFE TO CREATE TRUE TRACTION NON SLIP SURFACE:

We highly recommend that you practise and develop your technique to properly apply the aggregate on to our SKID SAFE Water Based Sealer/Finish by test applying it to any loose tiles, or small floor area before proceeding with the entire job area. Apply SKID SAFE following all of our directions to a section of the floor. This first coat can be applied on a small rectangle area which gives you plenty of room to hold a small amount of aggregate in your fingers and sprinkle it over the rectangle area of wet SKID SAFE. You can also hold a small amount of aggregate in your hand and slightly throw it up which will allow it to fall more evenly over the wet applied 1st coat of SKID SAFE. Repeat broadcasting the aggregate until the rectangle area of wet SKID SAFE has been completed to your satisfaction. Now, apply more SKID SAFE in a similar rectangle area and repeat these procedures above until the entire floor has been sealed with a first coat of SKID SAFE, and the aggregate has been broadcast onto it.

You may apply more aggregate onto the second coat of SKID SAFE when it is wet to make any aesthetic improvements in how much aggregate, or how the broadcast aggregate looks on the floor. Continue to top seal the floor area with a total of 6 coats of SKID SAFE applied according to our directions. After the final coat has dried to the touch, do not allow foot traffic on the floor for at least 8 hours. Cover the floor area with a cardboard so that it may CURE-get hard-for 96 hours. Then, remove the cardboard covering.

MAINTENANCE:

The floor may be cleaned daily using a neutral cleaner and water. You may powerwash the floor and pick up water/soil with a wetvac. Do not use disinfectants known to harm plastics/floor finishes.

CAUTION:

Irritates eyes and respiratory tract. Avoid inhalation and minimize exposure to dust. Overexposure may cause shortness of breath and lung injury. Avoid ingestion.

PRECAUTIONARY STATEMENTS:

Eyes: Safety glasses; Respiratory: Approved dust respirator. Protective gloves and clothing recommended

FIRST AID MEASURES:

Eyes: Wash with large amounts of water, Inhalation: Remove to fresh air. Get medical assistance if needed.

Ingestion: Obtain First Aid, or get medical assistance if needed.

CAUTION: KEEP OUT OF REACH OF CHILDREN!

Distributed by: New Dimensions Solutions, LLC, Las Vegas, NV 89169, (800) 731-2231, www.ndclean.com

NET CONTENT: 1 lb (16 oz) 5 lbs (80 oz) 10 lbs (160 oz)