

New Dimensions Solutions, LLC

# ONE COAT™

Water Based Primer/Sealer/Finish

HIGH GLOSS

- Protects Wood, Metals, Brass, Plastics, Vinyls, Signs, Masonry, and All Painted Surfaces
- Quick Drying PRIMER  
(One coat stops graffiti showing through new paint)

**Stops UV and Water Damage!**  
**PROTECTION YOU CAN COUNT ON!**  
**Guaranteed for 5 Years!**  
**Use Indoors and Outdoors!**  
**Safe and Pleasant to Use as Directed**  
**Unique Chemical Product Technology**  
**VERY MILD ODOR**

**CAUTION:**  
**MAY BE SKIN AND EYE IRRITANT**  
**Read All Cautions On Side Panel**  
**Before Using This Product**  
**KEEP OUT OF REACH OF CHILDREN!**

NET CONTENT

Quart (0.946 liter)  Gallon (3.784 liters)  5 Gallon (18.92 liters)

## PRIMER FOR ND GRAFFITI SHIELD SYSTEM™

Easy To Apply - Dries In Minutes  
Exceptional Durability - Very High Spread Rates  
(750 - 4000+ sq.ft. per gallon depending on porosity of the substrate)  
Low Use Cost (Only 4+ cents per sq.ft.)  
Stops Sun, Water and Most Chemical Damage  
Prevents Oxidation, Rust, Mold, Mildew and UV Damage  
Stain Resistant From Salt Water, Acids, Food Spills, Oils, etc.  
Does not Yellow, Crack, Peel, Flake, nor Chip  
Allows the Substrate to "Breathe"

ONE COAT™ works as a PRIMER, a SEALER and a FINISH to:

1. Protect paint from fading, chipping and cracking for many years
2. Restore faded paint and pigments like new
3. Effectively block off graffiti or any stains from showing through new paint
4. Quickly prime surfaces for painting
5. Colors do not fade/oxidize under ONE COAT™
6. Protects Metals, Brass, Plastics, Vinyls, Masonry, and Signs

## APPLICATION DIRECTIONS:

Thoroughly clean and dry all surfaces to be SEALED. A test application is strongly suggested to insure adequate surface preparation, spread rate, appearance (number of coats) and desired results.

Apply ONE COAT™ by spray, wax applicator, or soft sponge. ONE COAT™ will prime or block off graffiti and stains; 4 coats are suggested to restore and protect painted surfaces. Additional coats will increase the gloss. Spread ONE COAT™ gently and evenly so that it looks water clear. Do not rub it on the surface. After 15 minutes, or when dry to touch add a second application. Good ventilation will speed drying time. Do not use excessive water on sealed surfaces for 72 hours. The full cure time is 96 hours. Clean tools with water. Do not allow this product to freeze and do not use it in freezing temperatures. However, once ONE COAT™ is applied and cured, freeze/thaw cycles will have no effect on proper product performance.

**MAINTENANCE:** Clean with just water, or with a neutral cleaner.

**VOC CONTENT:** 19.6 g/l per California Regulations

**PRECAUTIONS:** Avoid contact with eyes and prolonged contact with skin. Avoid inhaling spray mist. If swallowed can cause irritation, nausea and diarrhea. Wear impervious gloves and safety goggles.

**FIRST AID:** Rinse eyes thoroughly for 15 minutes, pulling upper and lower lids apart. Rinse skin thoroughly with running water. If ingested DO NOT CAUSE VOMITING. Consult a Physician. If spray mist is inhaled, remove to fresh air.

**LIMITATION OF LIABILITY:** The user assumes full responsibility and risk in testing this product for the particular application. In no event shall NEW DIMENSIONS SOLUTIONS, LLC be liable for consequential or incidental damages exceeding the cost of this product.

MANUFACTURED BY: New Dimensions Solutions, LLC, Las Vegas  
NV 89169, (800) 731-2231, www.ndclean.com Date of manufacture: 05/22/07