

SUPER BOND & CLEAN™

- Cleans and Treats Ceramic Tiles & Grout Lines in 3 Minutes
- Insures Excellent Adhesion for SKID SAFE Water Based Sealer/Finish
- Prevents the Peeling of our Slip Resistant Floor Finish When the Floor is Washed

BIODEGRADABLE
No VOC's - NON FLAMMABLE
Very Slight Dull Odor
Contains No Acids

IMPORTANT:

DO NOT STORE NOR USE THIS PRODUCT BELOW 45°F!
Reheat this product if stored below 45° F.

CAUTION:

**CONTAINS FLURIDE SALTS THAT MAY BE HARMFUL OR FATAL
IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN, FROM
GLASS, METAL TRIM AND PLANTS.**
Read All Cautions On Side Panel Before Using This Product

NET CONTENT: QUART (0.946 liter) 5 Gallon (18.92 liters)

APPLICATION DIRECTIONS:

1. Test this product on a spare tile sample, or in a small inconspicuous area for suitability before treating the whole floor/wall. Read all Precautions and Directions thoroughly before using this product.

Precautions:

Adjacent areas must be properly protected when using this product. Though harmless to most building surfaces, the damage SUPER BOND & CLEAN™ causes to glass, soft metal is considered permanent. Cover all nearby windows and aluminum with plastic sheeting and plastic tape. Also, protect vegetation. SUPER BOND & CLEAN™ turns foliage brown on contact, and if drawn up through plants roots, it dehydrates and can kill them. Cover plants with plastic sheeting to keep concentrated SUPER BOND & CLEAN™ off foliage, and protect roots by either containing the rinse or trenching it away. **Wear rubber gloves and safety goggles. If working indoors ventilate the area.**

2. Strip old seals/finishes with a stripper to clear all pores of the grout lines and to clean and to strip tiles. Rinse the residue and neutralize the surface with a water-vinegar rinse of 4-1, or use a neutralizer. Let the floor dry.

3. Use a clean pre-rinsed and dried mop, or a quality sponge mop to apply SUPER BOND & CLEAN™ at full strength at about 400 sq.ft. per gallon (100 sq.ft. per quart). Do not mix it with water. Make sure that the floor/wall are all well covered with this product. Allow SUPER BOND & CLEAN™ to soak on the floor/wall for 3 minutes. Closely monitor the work area making sure that it is at all times thoroughly covered with the product, and treat only as big area as you can handle. **SUPER BOND & CLEAN™ must not dry out on tiles, or any surfaces.**

4. By gently scrubbing with a soft nylon brush and a lot of clean water remove all of the SUPER BOND & CLEAN™ from the wall/floor. Do this very thoroughly because all of the loose whitish residue has to be removed. Do not scrub hard! Repeat this procedure 3 times, or until there is not any whitish haze left on the tiles when they are dry.

5. Let the floor/wall dry for about an hour. When dry, the tiles should look dull, because there is now a frosting on them to create excellent adhesion for our SKID SAFE Water Based Sealer/Finish. If you see any whitish haze, or uneven looking appearance, repeat the step #4.

Note: If applying our GROUT COATING, do so now according to our directions for GROUT COATING..

6. Seal the tile floor/wall with 4 coats of SKID SAFE Water Based Sealer/Finish applied one coat at a time after each coat is **absolutely dry-to-the-touch**.

DO NOT STORE NOR USE THIS PRODUCT BELOW 45°F! Reheat this product if stored below 45° F.

FIRST AID: Rinse eyes thoroughly for 15 minutes and seek medical attention. Rinse skin thoroughly with running water. If ingested DO NOT INDUCE VOMITING. Drink large amounts of water. Call physician immediately.

LIMITATION OF LIABILITY: The user accepts full responsibility and risk in testing this product for the particular application. In no event shall NEW DIMENSIONS SOLUTIONS, LLC be liable for consequential or incidental damages exceeding the cost of this product.

Manufactured by: New Dimensions Solutions, LLC, Las Vegas, NV 89169
1-800-731-2231, www.ndclean.com Date of Manufacture: 05/22/07