

SECTION 1: IDENTIFICATION
1.1. Product Identifier
Product Name: SKID SAFE™

Formula: Proprietary Blend of Water, Acrylics and Solvents

1.2. Intended Use of the Product
Use of the substance/mixture: Water Based Sealer/Finish.

1.3. Name, Address, and Telephone of the Responsible Party
Company

 New Dimensions Solutions, LLC
 3960 Howard Hughes Parkway, Suite 500
 Las Vegas, NV 89169
 Phone: (800) 731-2231
 Fax: (800) 731-2231
 email: sales@ndclean.com
www.ndclean.com
1.4. Emergency Telephone Number
Emergency Number : (702) 943-8861

SECTION 2: HAZARDS IDENTIFICATION
2.1. Classification of the Substance or Mixture
Classification (GHS-US)

 Repr. 1B H360
 Aquatic Acute 3 H402
 Full text of H-phrases: see section 16

2.2. Label Elements
GHS-US Labeling
Hazard Pictograms (GHS-US) :


GHS08

Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H360 - May damage fertility or the unborn child.
 H402 - Harmful to aquatic life.

Precautionary Statements (GHS-US) : P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves, protective clothing, and eye protection.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

13.53 - 15.12 of the mixture consists of ingredients of unknown acute toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%
Dibutyl phthalate	(CAS No) 84-74-2	2.15
Tributyloxyethyl phosphate	(CAS No) 78-51-3	0.27

Full text of H-phrases: see section 16

SKID SAFE™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present, easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: May damage fertility. May damage the unborn child.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May damage fertility or the unborn child.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SKID SAFE™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Avoid temperatures above 177°C (350°F), the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature. Practice good housekeeping - spillage can be slippery on smooth surfaces either wet or dry.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors/spray. Avoid contact with skin, eyes and clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

Storage Temperature: 1 - 60 °C

7.3. Specific End Use(s)

Water Based Sealer/Finish.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters


For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

Dibutyl phthalate (84-74-2)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA IDLH	US IDLH (mg/m ³)	4000 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment : Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing : Chemically resistant materials and fabrics.

Hand Protection : Wear protective gloves.

Eye Protection : Chemical safety goggles.

Skin and Body Protection : Wear suitable protective clothing.

Respiratory Protection : If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information : When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance : Milky White Liquid, Active Material (Solid) Content: 15%

Odor : Mild acrylic odor

Odor Threshold : No data available

pH : 7.5 - 7.8 (@ 25 °C)

Evaporation Rate : No data available

Melting Point : No data available

SKID SAFE™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing Point	: 0 °C (32 °F) (Initial)
Boiling Point	: 100 °C (212 °F) (Estimate)
Flash Point	: Non-Combustible
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: 14 mm Hg @ 20°C (68°F) (Estimate)
Relative Vapor Density at 20 °C	: < 1 (Air = 1)
Relative Density	: No data available
Specific Gravity	: 1.04
Specific gravity / density	: 8.6 lb/gal
Solubility	: Product is dilutable
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
9.2. Other Information	
VOC content	: 19.6 g/l (per California VOC regulations)

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. **Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. **Hazardous Decomposition Products:** Combustion of the polymer film will yield acrylic monomers, and normal combustion products including carbon dioxide and carbon monoxide. Avoid breathing smoke or fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Dibutyl phthalate (84-74-2)	
LD50 Oral Rat	7499 mg/kg
LD50 Dermal Rabbit	> 20 ml/kg
LC50 Inhalation Rat	> 15.68 mg/l/4h
Tributyoxethyl phosphate (78-51-3)	
LD50 Oral Rat	3 g/kg
LD50 Dermal Rabbit	> 16 ml/kg
LC50 Inhalation Rat	> 6.4 mg/l/4h

Skin Corrosion/Irritation: Not classified

pH: 7.5 - 7.8 (@ 25 °C)

Serious Eye Damage/Irritation: Not classified

pH: 7.5 - 7.8 (@ 25 °C)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: May damage fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May damage fertility or the unborn child.

SKID SAFE™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Harmful to aquatic life.

Dibutyl phthalate (84-74-2)	
LC50 Fish 1	0.71 - 1.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas [fbw-through])
EC50 Daphnia 1	2.99 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	0.31 - 5.45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	3.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic fish	0.1 mg/l (Exposure time: 99 d - Species: Oncorhynchus mykiss [fbw-through])
Tributyloxyethyl phosphate (78-51-3)	
LC50 Fish 1	10.4 - 12.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [fbw-through])

12.2. Persistence and Degradability

SKID SAFE™	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

SKID SAFE™	
Bioaccumulative Potential	Not established.

Dibutyl phthalate (84-74-2)	
Log Pow	5.38 (at 25 °C)

Tributyloxyethyl phosphate (78-51-3)	
BCF fish 1	3.65
Log Pow	3.65 - 4.78

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology – Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

SKID SAFE™	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
Dibutyl phthalate (84-74-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %

Tributyloxyethyl phosphate (78-51-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2 US State Regulations

Dibutyl phthalate (84-74-2)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.

SKID SAFE™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - California - Proposition 65 - Reproductive Toxicity - Female	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	WARNING: This product contains chemicals known to the State of California to cause (Male) reproductive harm.

Dibutyl phthalate (84-74-2)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 06/16/2015
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Repr. 1B	Reproductive toxicity Category 1B
H360	May damage fertility or the unborn child
H402	Harmful to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)